

# Airpanel Select FZL


## Product Range



## Applications



## Filter Class



## KEY FACTS

- Self-stable, synthetic filter medium
- Several frame types available
- Easy assembly and handling
- Maintenance-friendly

## DESIGN

Pleated, synthetic filter medium, self-stable design, pleats are separated by hotmelt spacers to ensure stability.

## APPLICATIONS

Prefiltration for air-conditioning and ventilation equipment and/or systems. highly effective with coarse dust.

## OPTIONS

<b>Frame</b>	Polyester, metal or plastic
<b>Gasket</b>	Foamed polyurethane continuous gasket

# Airpanel Select

## FZL

### PERFORMANCE DATA

Article No.	Filter Class		Dimensions	Flow Rate	Pressure Drop
	ISO 16890	EN 779	mm	m <sup>3</sup> /h	Pa
800223023505	Coarse 70%	G4	285 x 592 x 24	475	35
800223023510	Coarse 70%	G4	492 x 592 x 24	825	35
800223023511	Coarse 70%	G4	492 x 622 x 24	875	35
800223023512	Coarse 70%	G4	592 x 592 x 24	1000	35
800223023514	Coarse 70%	G4	285 x 592 x 46	950	35
800223023518	Coarse 70%	G4	492 x 492 x 46	1375	35
800223023519	Coarse 70%	G4	492 x 592 x 46	1650	35
800223023520	Coarse 70%	G4	492 x 622 x 46	1750	35
800223023521	Coarse 70%	G4	592 x 592 x 46	2000	35
800223023522	Coarse 70%	G4	285 x 285 x 96	650	35
800223023526	Coarse 70%	G4	395 x 622 x 96	2075	35
800223023529	Coarse 70%	G4	492 x 622 x 96	2550	35
800223023530	Coarse 70%	G4	592 x 592 x 96	2900	35
800223062689	Coarse 80%	M5	285 x 592 x 46	950	45
800223062690	Coarse 80%	M5	492 x 492 x 46	1375	45
800223062691	Coarse 80%	M5	492 x 592 x 46	1650	45
800223062692	Coarse 80%	M5	492 x 622 x 46	1750	45
800223062693	Coarse 80%	M5	592 x 592 x 46	2000	45
800223062694	Coarse 80%	M5	285 x 285 x 96	650	45
800223062695	Coarse 80%	M5	395 x 622 x 96	2075	45
800223062696	Coarse 80%	M5	492 x 622 x 96	2550	45
800223061772	Coarse 80%	M5	592 x 592 x 96	2900	45

### SPECIFICATION

<b>Recommended air flow</b>	Flow rate ± 25 %	<b>Rec. final pressure for efficient energy use acc. to EN 13053</b>	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
<b>Heat resistance</b>	Max. 70 °C	<b>Moisture resistance</b>	100 % rel. humidity
<b>Regenerable</b>	No	<b>Incinerable</b>	Yes, except for metal frames